



**BlueDevil**®™

## BLUE DEVIL - PERFORMANCE DATA

1" BLUE DEVIL											
Nozzle	Position	Nozzle Flow		Effective Reach		Model	Swivel Inlet	Weight (ex coup)		Length (ex coup)	
		GPM	LPM	Feet	Metres			lbs	kg	in.	cm
BD 550	1	5	25	59	18	BD 550	1"	3.8	1.72	8	20
	2	15	50	82	25						
	3	30	100	92	28						
	4	50	175	101	31						
BD 1330	1	13	50	82	25	BD 1330	1"	3.8	1.72	8	20
	2	23	90	88	27						
	3	30	115	92	28						
BD 1560	1	15	55	82	25	BD 1560	1"	3.8	1.72	8	20
	2	30	110	92	28						
	3	45	170	101	31						
	4	60	225	112	34						
1½" BLUE DEVIL											
Nozzle	Position	Nozzle Flow		Effective Reach		Model	Swivel Inlet	Weight (ex coup)		Length (ex coup)	
		GPM	LPM	Feet	Metres			lbs	kg	in.	cm
BD 3012	1	30	115	85	26	BD 3012	1½"	4.2	1.91	9.2	23
	2	60	230	112	34						
	3	95	360	131	40						
	4	125	470	141	43						
BD 3015	1	30	115	85	26	BD 3015	1½"	4.2	1.91	9.2	23
	2	60	230	112	34						
	3	95	360	131	40						
	4	125	470	141	43						
	5	150	560	148	45						
BD 6015	1	60	230	112	34	BD 6015	1½"	4.2	1.91	9.2	23
	2	75	280	118	36						
	3	95	360	131	40						
	4	125	470	141	43						
	5	150	560	148	45						
BD 7515	1	75	280	118	36	BD 7515	1½"	4.2	1.91	9.2	23
	2	95	360	138	42						
	3	125	470	144	44						
	4	150	560	148	45						
2½" BLUE DEVIL											
Nozzle	Position	Nozzle Flow		Effective Reach		Model	Swivel Inlet	Weight (ex coup)		Length (ex coup)	
		GPM	LPM	Feet	Metres			lbs	kg	in.	cm
BD 9520	1	95	360	128	39	BD 9520	1½"	6.6	3	10.8	27
	2	125	470	141	43	BD 9520	2½"	6.9	3.13	11	28
	3	150	560	148	45						
	4	200	750	154	47						
BD 12250	1	125	470	131	40	BD 12250	2½"	7.9	12.5	12.5	32
	2	150	560	144	44						
	3	200	750	151	46						
	4	250	950	157	48						

Data measurements at 7 bar ≈ 100 psi