

INDUSTRIAL

W2540 Series

Lightweight Jet/Spray Branchpipes

AWG No. 1P

Simple jet/off/spray branchpipe; pipe, nozzle and tip manufactured from polyamide and fitted with a L/A inlet adaptor and ball valve.

Inlet: 2" BSP male thread easily adapted to a wide range of international fire connections.

Flow Rate: 130-230 l.p.m. at 6 bar inlet pressure depending on the nozzle tip in use.

Weight: 1.2kg (inc. B.I. coupling)

Dims: 445x80x167mm (inc. B.I. coupling)

AWG No. 1

Simple jet/off/spray branchpipe manufactured from polyamide and L/A and fitted with a L/A inlet adaptor and ball valve.

Inlet: 2" BSP male thread easily adapted to a wide range of international fire connections.

Flow Rate: 130-230 l.p.m. at 6 bar inlet pressure depending on the nozzle tip in use.

Weight: 1.5kg (inc. B.I. coupling)

Dims: 453x80x161mm (inc. B.I. coupling)

AWG No. 2

Simple jet/off/spray branchpipe manufactured from polyamide and L/A and fitted with a L/A inlet adaptor and ball valve.

Inlet: 2" BSP male thread easily adapted to a wide range of international fire connections.

Flow Rate: 400 l.p.m. at 6 bar inlet pressure.

Weight: 2.1kg (inc. coupling)

Dims: 514x92x169mm (inc. B.I. coupling)

For all models shown:

Maximum w.p. 16 bar

Test Pressure 24 bar

W2540 Series

