



PROFESSIONAL/FIRST RESPONDER

# EXTREME



For Instruction  
video scan QR Code

### Product Information

- Isolate and extinguish small fires.
- Blocks any fire, even small lithium battery fires.
- Multipurpose
- Immediately isolated toxic gases and smoke, protecting civilians from carcinogen exposure
- Comes in a smart bag
- Requires no maintenance.
- Metal chain integrated to add weight for easier use.



### Ideal for:

Battery fires - Restaurant kitchens – Industry tools – The recycling industry – Car manufacturers – Workshops – Shops or businesses that store small or large amounts of lithium batteries - Battery manufacturers- Marine - Aviation - Military

### Sizes:

<b>Small:</b>	<b>Medium:</b>
± 1.5 x 1.5 m	± 3 x 3 m
± 7.5kg	± 21kg

How to use Handled by:

1. Take the fire blanket out of the smartbag.
2. Gently cover the burning object.
3. Make sure the fire blanket is tight all the way around the burning object. Wait at least 20 minutes.

For fire in electric scooter/tools etc. wait for firefighters to assess the situation further!



**ALWAYS CALL THE FIRE DEPARTMENT!**



**BRIDGEHILL®**  
WE SIMPLY BLOCK FIRE



TECHNICAL SHEET

**EXTREME**

**FOR PROFESSIONALS & STANDBY/PREPAREDNESS**

<b>SKU:</b>	<b>Extreme Small:</b> 504210	<b>Medium:</b> 504211
<b>Sizes/Weight:</b>	<b>Small:</b> ± 1.5 x 1.5m ± 7.5 kg	<b>Medium:</b> ± 3 x 3m ± 21 kg
<b>Core material:</b>	Six-layer solution. Four Layers of Bridgetech™ coating, 2 layers of extreme pyroxene.	
<b>Coating:</b>	± 550 gsm silicon polymer (Flames may occur during first time use) In fires with high levels of conduction heat, flames may appear from the coating of the blanket. This will not alter the purpose of the blanket.	
<b>Edge on blanket:</b>	Metal chain sewed in around the edges to add weight	
<b>Main usage:</b>	Blocks any small fire, even lithium battery fire	
<b>Smart bag:</b>	Airtight bag. Smart bag care and maintenance: Use silicon grease on the zipper to keep the bag airtight and smell free.	

TECHNICAL SPECIFICATION

Core Fabric			Unit	Tolerance
Yarn	Warp	300	Tex	± 5
	Weft	165	Tex	± 5
Yarn count	Warp	8	Ends/cm	± 5
	Weft	8	Ends/cm	± 5
Tensile strength	Warp	3200	N/50mm	≥
	Weft	2500	N/50mm	≥
Area weight	–	1200	G/m2	± 10%
Thickness	–	0.40	Mm	± 5%
Weave pattern	–			4H satin
Service temperature on core fabric	Short Term ± 1600 °C Long Term ± 800 °C			