



**W151030 - series  
FHT Portable Mini-Monitor  
non-adjustable**

At less than 4kg, the FHT Mini Monitor is simple and compact for easy storage and handling, offering a virtually maintenance free solution to static water application. Its simplicity makes it an extremely cost-effective piece of equipment.

Manufactured in Sched. 40 mild steel, the body is polyester powder coated for corrosion resistance. Coupled to suit a customer's requirement, the elevator plate features a 13mm hole to allow the attachment of a restraining tether or eyebolt (supplied by others).

Inlet and outlet connectors, typically instantaneous to BS336 but can specified by customer.

Maximum w.p. - 16 bar.

Test Pressure - 24 bar.



W151031

**W151010  
Portable Mini-Monitor - adjustable**

At 7kg, this adjustable Mini Monitor is another compact design for easy storage and handling. Elevation is adjustable from 30o - 50o and can be locked by a lever handle.

Manufactured in L/A painted hammer finish red, it can be supplied with an anodized finish for extra protection against aggressive foam compounds.

Inlet and outlet connectors typically instantaneous to BS336.

Maximum w.p. - 16 bar.

Test Pressure - 24 bar.

Both monitors can easily be fitted with a hand branch nozzles to give a rapidly deployed, low maintenance, cost-effective solution.



W151010 with branch