



# Standpipes

## W3510 Series Standpipes Plug-In, Swivel & Anti-Siphon

### W3510 series

#### Standpipes: Plug-in & Swivel Models

Light Alloy

**Single Head** Emergency type.  
**Inlet:** 2½" female hydrant round thread (HRT) fixed (BS750).  
**Outlet:** 2½" female inst BS336 single twist release - plug-in or swivel type.

**Double Head** Emergency type.  
**Inlet:** 2½" female hydrant round thread (HRT) fixed (BS750).  
**Outlets:** 2 x 2½" female inst BS336 single twist release - swivel type or plug-in. One outlet fitted with L/A blank plug and chain.

**Single and Double Head Anti-Siphon.**  
 Plug-in head c/w 2" N.B. Brass double check valve to BS6282 Part 5 including check port.

**Inlet:** 2½" female hydrant round thread (HRT) fixed (BS750).  
**Outlet(s):** 1 or 2 x 2½" female inst BS336 single twist release - usually plug-in.

Other inlet connections are available including ball, bayonet and Belfast. Spare heads can also be supplied giving flexibility in the field for the plug-in models.

Maximum w.p. 16 bar  
 Test Pressure 24 bar

Outlet	Check Valve	Head Connection	Height	Code No.
Single Head	N/A	Swivel	851 mm	W351001F
	N/A	Plug-in	851 mm	W351003F
Double Head	N/A	Swivel	851 mm	W351021F
	N/A	Plug-in	851 mm	W351023F
Single Head	50mm Brass	Swivel		
		Plug-in	965 mm	W351011
Double Head	50mm Brass	Swivel		
		Plug-in	945 mm	W351013



W351011

W351001F



W351013

